

Battery Specification

International Model Size		Max Dimension	Weight	Nominal Voltage	Nominal Capacity			Max Continuous Operating Current	Max Pulse Discharge Current
Model No.	Size	[mm]	[g]	[V]	End Voltage [V]	Nominal Discharge Current [mA]	Capacity [mAh]	[mA]	[mA]

Bobbin Type

ER10250		Φ10.4 X 25.0	5	3.6	2	0.5	400	5	10
ER10280		Φ10.4 X 28.0	6	3.6	2	0.5	450	10	20
ER10450		Φ10.4 X 45.0	9	3.6	2	0.5	800	25	60
ER13150		Φ13.5 X 15.7	7	3.6	2	0.5	450	10	20
ER13170		Φ13.5 X 17.8	7	3.6	2	0.5	500	10	20
ER14250	1/2AA	Φ14.5 X 25.2	11	3.6	2	0.5	1200	20	50
ER14335	2/3AA	Φ14.5 X 33.5	13	3.6	2	1.3	1650	30	70
ER14505	AA	Φ14.5 X 50.5	19	3.6	2	1	2600	50	100
ER17335	2/3A	Φ17.0 X 33.5	18	3.6	2	1	2100	50	100
ER17505	A	Φ17.5 X 50.5	24	3.6	2	1	3600	70	150
ER18505		Φ18.5 X 50.5	29	3.6	2	2	4100	80	150
ER26500	C	Φ26.2 X 50.0	53	3.6	2	4	8500	100	200
ER34615	D	Φ34.2 X 61.5	105	3.6	2	3	19000	150	300
ER261020	CC	Φ26.0 X 102.0	100	3.6	2	3	16000	200	400
ER341245	DD	Φ34.2 X 124.5	200	3.6	2	10	35000	400	500

Spiral Type

ER14250M		Φ14.5 X 25.0	11	3.6	2	0.5	800	100	250
ER14335M		Φ14.5 X 33.5	14	3.6	2	1	1350	200	500
ER14505M		Φ14.5 X 50.5	20	3.6	2	3	2100	300	1000
ER17335M		Φ17.0 X 33.5	20	3.6	2	4	1700	300	1000
ER17505M		Φ17.0 X 50.5	28	3.6	2	3	2800	400	1000
ER18505M		Φ18.5 X 50.5	30	3.6	2	3	3500	500	1500
ER26500M		Φ26.2 X 50.5	58	3.6	2	10	6000	1000	2000
ER34615M		Φ34.2 X 61.5	115	3.6	2	10	13000	2000	3000